

AC244 Series

Premium Miniature Industrial Accelerometer, High Frequency, Side Exit 2 Pin Mini-MIL Connector, 100 mV/g, ±5%



VIBRATION ANALYSIS HARDWARE



Product Features

Premium mini mil, Low Profile Industrial Accelerometer


100 mV/g ± 5% Sensitivity

- ▶ 2 Pin Mini-MIL Connection or Integral Cable
Note: Integral Cable Options are only for Permanent Monitoring Applications

AC244-1D

2 Pin Mini Mil Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

AC244-2D

CB110 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC244-3D

CB206 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC244-6D

CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC244	M/AC244	Environmental		
Sensitivity (±5%)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	36-900,000 CPM	0,6-15000 Hz	Maximum Shock Protection		5,000 g, peak
Frequency Response (±10%)	60-600,000 CPM	1,0-10000 Hz	Electromagnetic Sensitivity		CE
Frequency Response (±5%)	120-420,000 CPM	2,0-7000 Hz	Sealing		Welded, Hermetic
Dynamic Range		± 50 g, peak	Submersible Depth	200 ft.	60 m
Electrical			Physical		
Settling Time		<2.5 seconds	Sensing Element		PZT Ceramic
Voltage Source (IEPE)		18-30 VDC	Sensing Structure		Shear Mode
Constant Current Excitation		2-10 mA	Weight	2.1 oz	60 grams
Spectral Noise @ 10 Hz		30 µg/√Hz	Case Material		316L Stainless Steel
Spectral Noise @ 100 Hz		4 µg/√Hz	Mounting		1/4-28
Spectral Noise @ 1000 Hz		2 µg/√Hz	Connector (Non-Integral)		2 Pin mini-MIL (J Series)
Output Impedance		<100 ohm	Resonant Frequency	1,192,600 CPM	26000 Hz
Bias Output Voltage		7-14 VDC	Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Case Isolation		>10 ⁸ ohm	Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate		CA10