

# AC936 Series

Low Capacitance, Class I, Division 2 / Zone 2 Accelerometer, Side Exit 2 Pin Connector, 100 mV/g, ±10%



VIBRATION ANALYSIS HARDWARE



## Regulatory Information

Ex nA IIC T3/T4  
 AEx nA IIC T3/T4  
 CLI Groups A, B, C, D  
 CLII Groups F, G  
 CLIII


Ui = 28 Vdc Ii = 100 mA  
 CSA 221421  
 KEMA 04ATEX1066  
 Ex nA II T3 or T4

Operating Temperature Code: T3  
 Ambient Temperature Range =  
 -40 to 125°C

Operating Temperature Code: T4  
 Ambient Temperature Range =  
 -40 to 80°C

### AC936-1A 2 Pin Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

### AC936-2C CB190 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

### AC936-3C CB206 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC936	M/AC936	<b>Environmental</b>		
Sensitivity (±10%)		100 mV/g	Temperature Range	-40 to 250°F	-40 to 121°C
Frequency Response (±3dB)	30-516,000 CPM	0.5-8600 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	60-360,000 CPM	1.0-6000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range		± 80 g, peak	Sealing	Welded, Hermetic	
<b>Electrical</b>			SIL Rating	SIL 2	
Settling Time		<3 Seconds	<b>Physical</b>		
Voltage Source (IEPE)		18-28 VDC	Sensing Element	PZT Ceramic	
Constant Current Excitation		2-10 mA	Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz		30 µg/√Hz	Weight	5.3 oz	150 grams
Spectral Noise @ 100 Hz		19 µg/√Hz	Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz		15 µg/√Hz	Mounting	1/4-28	
Output Impedance		<100 ohm	Connector (Non-Integral)	2 Pin MIL-C-5015	
Bias Output Voltage		10-14 VDC	Resonant Frequency	1,260,000 CPM	21000 Hz
Case Isolation		>10 <sup>8</sup> ohm	Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
			Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate		CA10